IDAHO DEPARTMENT OF WATER RESOURCES WELL DRILLER'S REPORT

Office Use Only												
Inspected by												
Twp			Rge	Se								
	1/4		1/4 _									
Lat:	:	:	Long:	:	:							

1. WELL TAG NO. D0033898		ELL TE		Dailes Z	Air Flowing Art				
DRILLING PERMIT N 819876	Pump						Time		
Other IDWR No	Yield gal./min.		-	Drawdown 100%	195	2 Hou			
2. OWNER:	-	40	+	100%	195	21100	410	\dashv	
Name Eagle Tree Group	-		-					\neg	
Address PO Box 1496					D-Hh-l	I - 40 mm	Cold		
City Tacoma State WA Zip 98401	Water Temp. Cold Bottom hole temp. Cold Water Quality test or comments: (below) Depth first Water Encountered 106								
3. LOCATION OF WELL by legal description:					ow) Depth first Water b	encountered		00	
N Twp 50N North ✓or South ☐		light Bro		A STATE OF THE PERSON NAMED IN COLUMN 1					
Rge 05W East □ or West ✔	12. LI	THOLO	andonme	ent)					
Sec 13 1/4 NW 1/4 SE 1/4	Bore			Remarks: Lithology, Water Quality and Temperature			Wa	ater	
W E 10 Ac 40 Ac 160 Ac			То	Lithology,	Lithology, water Quality and Temperature				
Gov't Lot County Kootenai	8	0	2	Topsoil				V	
Lat Long	8	2	10	Granite: Gra	y Medium			V	
	. 8	10	22	Granite: Brown Soft				1	
S Address of Well Site: (see next line)	8	22	24	Granite: Gray Medium				~	
West Star Light Road City Post Falls	6	24	54	Granite: Gray Medium				V	
Lot 10 Blk Sub. Name (see next line)	6	54	57	Granite: Gre	en Soft			V	
Sundown Estates Lot #10	6	57	106	Granite: Gra				V	
4. USE:	6	106	109	Grannite: Br	own Soft Broken (6GPN	A)	V		
✓ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation	6	109	121	Granite: Gra	y Medium			V	
☐ Thermal ☐ Injection ☐ Other	6	121	124	Granite: Bro	ken (15GPM)		V		
5. TYPE OF WORK check all that apply (Replacement etc.)	6	124	158	Granite: Gra				V	
✓ New Well ☐ Modify ☐ Abandonment ☐ Other	6	158	160	Granite: Bro	ken (19GPM)		V		
6. DRILL METHOD	6	160	200	Granite: Gra	ay Medium			V	
SEAL/FILTER PACK Material From To Sacks/Lbs Bentonite Grans 0 24 4 sacks Dry Pour Drive Shoe Used? ✓ Y □ N Shoe Depth(s) 25 Drive Shoe Seal Tested? □ Y ✓ N How? 8. CASING/LINER Diam From To Gauge Material Casng Liner Weld Thrdec 6 +1 25 0.250 Steel ✓ □ ✓ □ ✓ □ ✓ □ ✓ □ ✓ □ ✓ □ ✓ □ ✓ □ ✓				J	CEIVED UL 29 & 4 DWE-Eloth				
Longar Housepipe									
9. PERFORATIONS/SCREENS ✓ Perforations? Method Drilled Liner ☐ Screens? Screen Type	_	Completed Dept 200 (Me Date: Started 7/8/2004 Completed 7/9/200						able)	
The Late Andrew Motorial Cooper Lines	42	ווימח	EDS C	CERTIFICA	TION				
140 200 3/8" 200 4" PVC	I/We	certify the	nat all m ig was i	ninimum well o removed.	construction standards v	were compli		ith at	
ADTECIAL PRESCUE	Firm		Jnited D	Orilling Inc.	11 11			~+ 1*	
10. STATIC WATER LEVEL or ARTESIAN PRESSURE 80 ft. below ground. Artesian pressurelb.		e – Official	Ta	m	Valle	Date	7/1:	3/200	
Depth flow encountered 160 ft. Describe access port of control devices: Steel Cap Welded	r and Sup	ervisor o	r Opera	ator Curtis S.	Hammond	Date	7/1	3/200	