



WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

1. GENERAL AND WELL LOCATION	OSE POD NO. (WELL NO.) RG-A1223		WELL TAG ID NO.		OSE FILE NO(S).		
	WELL OWNER NAME(S) Kevin A Yockers				PHONE (OPTIONAL)		
	WELL OWNER MAILING ADDRESS P.O Box 238				CITY Placitas	STATE NM	ZIP 87043
	WELL LOCATION (FROM GPS)	DEGREES 35		MINUTES 18	SECONDS 47	* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84	
		LATITUDE		N			
LONGITUDE		106		25		30 W	
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE Camino de Las Huertas Placitas NM							

2. DRILLING & CASING INFORMATION	LICENSE NO. 547	NAME OF LICENSED DRILLER Thomas Lujan			NAME OF WELL DRILLING COMPANY Lujan Water Well Service			
	DRILLING STARTED 4/29/2023	DRILLING ENDED 4/29/2023	DEPTH OF COMPLETED WELL (FT) 300'	BORE HOLE DEPTH (FT) 300'	DEPTH WATER FIRST ENCOUNTERED (FT) 144'			
	COMPLETED WELL IS: <input type="checkbox"/> ARTESIAN *add Centralizer info below <input type="checkbox"/> DRY HOLE <input checked="" type="checkbox"/> SHALLOW (UNCONFINED)				STATIC WATER LEVEL IN COMPLETED WELL (FT) 135	DATE STATIC MEASURED 5/18/2023		
	DRILLING FLUID: <input checked="" type="checkbox"/> AIR <input type="checkbox"/> MUD ADDITIVES - SPECIFY:							
	DRILLING METHOD: <input type="checkbox"/> ROTARY <input checked="" type="checkbox"/> HAMMER <input type="checkbox"/> CABLE TOOL <input type="checkbox"/> OTHER - SPECIFY:						CHECK HERE IF PITLESS ADAPTER IS INSTALLED <input checked="" type="checkbox"/>	
	DEPTH (feet bgl)		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE (add coupling diameter)	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
	FROM	TO						
+20'	40'	12.75"	Steel	Welded	8-1/4"	.188	Blank	
5'	240'	7.5"	SDR17	Spline Lock	4.5"	.29	Blank	
240'	280'	7.5"	SDR 17	Spline Lock	4.5"	.29	.032	
280'	300'	7.5"	SDR 17	Spline Lock	4.5"	.29	Blank	

3. ANNULAR MATERIAL	DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL <i>*(if using Centralizers for Artesian wells- indicate the spacing below)</i>	AMOUNT (cubic feet)	METHOD OF PLACEMENT
	FROM	TO				
	5'	40'	12.75"	Bentonite hole plug	252 pounds	Tremie
	30'	300'	7.5"	3/8" Round gravel		Surface pour

FOR OSE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 09/22/2022)

FILE NO.	POD NO.	TRN NO.
LOCATION	WELL TAG ID NO.	PAGE 1 OF 2

