Form 238-7
7/94

POSTED

IDAHO DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORT

RECEIVED
Use Typewriter or Ball Point Pen
APR 24 1995
NORTHERN REGION
IDWR

95-95-N-0036-000

1. DRILLING PERMIT NO. 95 - 95 - N - 0036 - 000
Other IDWR No.

2. OWNER:
Name TAGGART, JOE
Address E 4925 BOEKEL ROAD
City RATHDRUM State ID Zip 83858

3. LOCATION OF WELL by legal description:
Sketch map location must agree with written location.

N / W / E / S — X

Twp. 51 North ☒ or South ☐
Rge. 03 East ☐ or West ☒
Sec. 04 , 1/4 NE (10 acres) 1/4 NE (40 acres) 1/4 NE (160 acres)
Gov't Lot County KOOTENAI

Address of Well Site
City
(Give at least name of road + Distance to Road or Landmark)

Lt. 001 Blk. 001 Sub. Name HAYDEN ACRES

4. PROPOSED USE:
☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other

5. TYPE OF WORK
☒ New Well ☐ Modify or Repair ☐ Replacement ☐ Abandonment

6. DRILL METHOD
☐ Mud Rotary ☒ Air Rotary ☐ Cable ☐ Other

7. SEALING PROCEDURES

SEAL/FILTER PACK Material	From	To	AMOUNT Sacks or Pounds	METHOD
BENTONITE	0	110	2 SACKS	POWDER
BENTONITE	0	110	2 SACKS	CRUMBLES

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s)
Was drive shoe seal tested? Y ☐ N ☒ How?

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6	+2	185	.250	STEEL	☒	☐	☒	☐
					☐	☐	☐	☐
					☐	☐	☐	☐

Length of Headpipe Length of Tailpipe

9. PERFORATIONS/SCREENS
☒ Perforations Method TORCH CUT
☐ Screens Screen Type

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
165	185	1/16	60	6	STEEL	☐	☐
						☐	☐
						☐	☐

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:
100 ft. below ground Artesian pressure lb.
Depth flow encountered ft. Describe access port or control devices:

NENE 4 51N 3W

11. WELL TESTS:
☐ Pump ☐ Bailer ☒ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
25+			2 HRS

Water Temp. COLD Bottom hole temp.
Water Quality test or comments: GOOD & CLEAN

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Water Y	Water N
8	0	1	TOPSOIL BROWN SOFT		X
8	1	41	CLAY TAN BROWN MED.		X
8	41	110	CLAY TAN YELLOW MED		X
8	110	158	BASALT BLACKISH HARD		X
8	158	168	BASALT BLACKISH FRACTURED	X	
8	168	180	BASALT BLACKISH HARD		X
8	180	185	CLAY BLACK SOFT		X
			1x6" Well Seal - Bolt On		
			3/8 Pea Gravel From 100'-185'		

Completed Depth 185 (Measurable)
Date: Started 04/12/95 Completed 04/12/95

13. DRILLER'S CERTIFICATION
I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name H2O WELL SERVICE, INC. Firm No. 448
Firm Official John Mahoney Date 04/19/95
and
Supervisor or Operator Mark L. Lee Date 04/19/95
(Sign once if Firm Official & Operator)

FORWARD WHITE COPY TO WATER RESOURCES