

WELL RECORD & LOG

OFFICE OF THE STATE ENGINEER

www.ose.state.nm.us

Corrected

STATE DEPT. OFFICE
BUREAU OF RECORDS

22 JUN 10 PM 3:30

					OSE FILE NUMBER(S) RG 94413 POD 1		
WELL OWNER NAME(S) DETHOMAS REVOCABLE TRUST/ROSEMARY SEGURA-DETHOMAS TRUSTEE					PHONE (OPTIONAL)		
WELL OWNER MAILING ADDRESS 11 QUAIL MEADOW ROAD					CITY PLACITAS NM 87043		
WELL LOCATION (FROM GPS)		DEGREES MINUTES SECONDS LATITUDE 35 18 10.52 N LONGITUDE 106 27 13.28 W		* ACCURACY REQUIRED: ONE TENTH OF A SECOND * DATUM REQUIRED: WGS 84			
DESCRIPTION RELATING WELL LOCATION TO STREET ADDRESS AND COMMON LANDMARKS - PLSS (SECTION, TOWNSHIP, RANGE) WHERE AVAILABLE							

LICENSE NUMBER WD-672		NAME OF LICENSED DRILLER THOMAS MURRAY		NAME OF WELL DRILLING COMPANY MURRAY DRILLING COMPANY	
DRILLING STARTED 5/22/14	DRILLING ENDED 5/29/14	DEPTH OF COMPLETED WELL (FT) 535' 470'	BORE HOLE DEPTH (FT) 535' 470'	DEPTH WATER FIRST ENCOUNTERED (FT) 360	
COMPLETED WELL IS: ☐ ARTESIAN ☐ DRY HOLE ☒ SHALLOW (UNCONFINED)				STATIC WATER LEVEL IN COMPLETED WELL (FT) 230	
DRILLING FLUID: ☒ AIR ☐ MUD ☐ ADDITIVES - SPECIFY:					
DRILLING METHOD: ☒ ROTARY ☐ HAMMER ☐ CABLE TOOL ☐ OTHER - SPECIFY:					

DEPTH (feet bgl)		BORE HOLE DIAM (inches)	CASING MATERIAL AND/OR GRADE (include each casing string, and note sections of screen)	CASING CONNECTION TYPE	CASING INSIDE DIAM. (inches)	CASING WALL THICKNESS (inches)	SLOT SIZE (inches)
FROM	TO						
0	495	7 7/8	SCH 40 PVC	LOCK/GLUE	4	.237	
495	535' 470'	7 7/8	SCH 40 PVC	LOCK/GLUE	4	.237	.030

DEPTH (feet bgl)		BORE HOLE DIAM. (inches)	LIST ANNULAR SEAL MATERIAL AND GRAVEL PACK SIZE-RANGE BY INTERVAL	AMOUNT (cubic feet)	METHOD OF PLACEMENT
FROM	TO				
535' 470'	295	7 7/8	8-12 COLORADO SILICA SAND	120	TOP LOAD
295	40	7 7/8	DRILL CUTTINGS	41	TOP LOAD
40	5	7 7/8	HOLE PLUG	7	TREMIE

FOR USE INTERNAL USE

WR-20 WELL RECORD & LOG (Version 06/08/2012)

FILE NUMBER		POD NUMBER	TRN NUMBER
LOCATION			PAGE 1 OF 2

PAGE 1 OF 2

PAGE 2 OF 2